



Geschaafd	B	D	255	270	300	330	360	390	420	450	480	510	540	570	600
Vuren C 21.5x48 geëgliseerd en gebost	22	50		454	1299	6282	595	734	21	1065	1712	6663	254	1417	138
Vuren C24 geschaafd circa 30x170mm	32	175					36	51	368	132	268	16	628		
Vuren C24 geschaafd circa 30x195mm	32	200					216	222	501	529	280	420	518		
Vuren C24 geschaafd circa 30x220mm	32	225					277	324	440	403	318	304	3		
Vuren C24 geschaafd circa 30x245mm	32	250					103	231	187	190	257	784	418		
Vuren C24 geschaafd circa 38x089mm	38	89	972		179	1	989	321	1752	1265	2443	833		2	1
Vuren C24 geschaafd circa 38x120mm	38	120	936		77	894	415	443	96	539	372	116	791		
Vuren C24 geschaafd circa 38x140mm	38	140			74	81	68	91	206	177	59		829		
Vuren C24 geschaafd circa 38x170mm	38	170				121	257	1	15	217	525	375	440	1	55
Vuren C24 geschaafd circa 36x170mm	38	175			18	60					33	176	240		
Vuren C24 geschaafd circa 38x184mm	38	184				163	84		381	376	700		8		
Vuren C24 geschaafd circa 36x195mm	38	200					1	209	281	291	307	109	231		
Vuren C24 geschaafd circa 36x220mm	38	225				337	140		389	272	112	172	280		
Vuren C24 geschaafd circa 38x235mm	38	235			14	336	6	279	453	525	545	914	1123	1	726
Vuren C24 geschaafd circa 36x245mm	38	250					103	231	360	4	199	331	206		

Gevingerlast	B	D	540	570	600	660	700	750	800	840	850	900	1000
Gevingerlast KOMO C24, geschaafd op circa 30x170mm	32	175		39	182	164		164				166	
Gevingerlast KOMO C24, geschaafd op circa 30x195mm	32	200		316	332	177		160				146	
Gevingerlast KOMO C24, geschaafd op circa 30x220mm	32	225		508				111				160	
Gevingerlast KOMO C24, geschaafd op circa 30x245mm	32	250		282	169	259		436				495	
Gevingerlast KOMO C24, geschaafd op circa 30x270mm	32	275		588	646	241						139	64
Gevingerlast KOMO C24, geschaafd op circa 38x170mm	38	170		168	23	133		171		72		200	
Gevingerlast KOMO C24, geschaafd op circa 36x170mm	38	175		104	183	168		156				161	
Gevingerlast KOMO C24, geschaafd op circa 38x184mm	38	184	329					164					
Gevingerlast KOMO C24, geschaafd op circa 36x195mm	38	200		111	162	45		31				60	
Gevingerlast KOMO C24, geschaafd op circa 36x220mm	38	225		370	244	170		129				291	
Gevingerlast KOMO C24, geschaafd op circa 38x235mm	38	235	995	347	962	432	280	332				257	
Gevingerlast KOMO C24, geschaafd op circa 36x245mm	38	250		328	205	147		195				135	
Gevingerlast KOMO C24, geschaafd op circa 36x270mm	38	275		152	124	253		374					56
Gevingerlast KOMO C24, geschaafd op circa 38x285mm	38	285		13		49		243				300	
Gevingerlast KOMO C24, geschaafd op circa 44x270 mm	47	275		99	90	51		11				99	40