



Geschaafd	B	D	270	300	330	360	390	420	450	480	510	540	570	600
Vuren C 21.5x48 geëgliseerd en gebost	22	50	2146	2174	5944	5088	860	1175	174	570	30	324		128
Vuren C24 geschaafd circa 30x170mm	32	175				73	192	134	205	196	43	138		
Vuren C24 geschaafd circa 30x195mm	32	200				175	206		463	240	349	423		
Vuren C24 geschaafd circa 30x220mm	32	225				225	243	416	401	89	105	1		
Vuren C24 geschaafd circa 30x245mm	32	250					51	320	185	176	181	715		
Vuren C24 geschaafd circa 38x089mm	38	89	1248	260	156	944	110	1644	881	1270	502			
Vuren C24 geschaafd circa 38x120mm	38	120		99	591	107	257	320	377	156	507	1219	225	1377
Vuren C24 geschaafd circa 38x140mm	38	140		126	47	562	154	107	351	85	430	1871	151	672
Vuren C24 geschaafd circa 38x170mm	38	170				60	135	323		181	501	3	1	9
Vuren C24 geschaafd circa 36x170mm	38	175			6	91	48	154	84	161	254	103		
Vuren C24 geschaafd circa 38x184mm	38	184			93	293	286	300	416	248	1	28	4	
Vuren C24 geschaafd circa 36x195mm	38	200					153		53	341	3			
Vuren C24 geschaafd circa 36x220mm	38	225				47	410	412	218	229	216	65		
Vuren C24 geschaafd circa 38x235mm	38	235				177	271	236	23	602		45	9	1449
Vuren C24 geschaafd circa 36x245mm	38	250					5	78		4	40	95		

Gevingerlast	B	D	570	600	660	700	750	800	840	900	1000			
Gevingerlast KOMO C24, geschaafd op circa 30x170mm	32	175	48	178	61		1			5				
Gevingerlast KOMO C24, geschaafd op circa 30x195mm	32	200	310	238	235		142			281				
Gevingerlast KOMO C24, geschaafd op circa 30x220mm	32	225	144	223	160		231			130				
Gevingerlast KOMO C24, geschaafd op circa 30x245mm	32	250	261	320	375					3				
Gevingerlast KOMO C24, geschaafd op circa 30x270mm	32	275	127	297	263		10			324	26			
Gevingerlast KOMO C24, geschaafd op circa 38x170mm	38	170			60		60		168	84				
Gevingerlast KOMO C24, geschaafd op circa 36x170mm	38	175	69	81	153		113			112				
Gevingerlast KOMO C24, geschaafd op circa 38x184mm	38	184			286		63			51				
Gevingerlast KOMO C24, geschaafd op circa 36x195mm	38	200	210	283	130		224			278				
Gevingerlast KOMO C24, geschaafd op circa 36x220mm	38	225	336	307	160		256	56		142				
Gevingerlast KOMO C24, geschaafd op circa 38x235mm	38	235			32	484	15			242				
Gevingerlast KOMO C24, geschaafd op circa 36x245mm	38	250	310	216	437		518			204				
Gevingerlast KOMO C24, geschaafd op circa 36x270mm	38	275		564	387		24			338	44			
Gevingerlast KOMO C24, geschaafd op circa 38x285mm	38	285		113	80					53				
Gevingerlast KOMO C24, geschaafd op circa 44x270 mm	47	275	106	124	194		101			86	42			