



Ruwhout	B	D	300	330	360	390	420	450	480	510	540	570	600
Ruwhout, 022x100, Vuren, C, Ruw	22	100	10686	439		5565	5958	9188	5945	620	2178	27	



Geschaafd	B	D	270	300	330	360	390	420	450	480	510	540	570	600
Vuren C 21.5x48 geëgliseerd en gebost	22	50		70	3816	299	4897				1736			
Geschaafd, 022x050, Vuren, Ventilatielat gewolman...	22	50					111	459						
Vuren C geschaafd circa 30x45mm	32	50		119		336		522		830	881	393		
Vuren ventilatielat 28x45 mm hoh 400mm 7x40 gewo...	32	50					4			3369				
Vuren geschaafd op 28x45mm gewolmaniseerd	32	50							1358		770			
Vuren C24 geschaafd circa 30x170mm	32	175				63	171	227	176	135	79			
Vuren C24 geschaafd circa 30x195mm	32	200				48	235	155	397	53	11	32		
Vuren C24 geschaafd circa 30x220mm	32	225				4			54	142	79	228		
Vuren C24 geschaafd circa 30x245mm	32	250					5	80	123	239	274			
Vuren C24 geschaafd circa 38x089mm	38	89			293	609	649	149	508	431	855	884	60	
Vuren C24 geschaafd circa 38x120mm	38	120		206	116		136	358	385	560	189	164	28	664
Vuren C24 geschaafd circa 38x140mm	38	140	82	164			111	70	294	358	615	90	149	6
Vuren C24 geschaafd circa 38x170mm	38	170					56		2		75			1182
Vuren C24 geschaafd circa 36x170mm	38	175						218	198	171	218	191		
Vuren C24 geschaafd circa 38x184mm	38	184			216	702	161	327	154	201	449	495	3	
Vuren C24 geschaafd circa 36x195mm	38	200						107	121	97	159	115		
Vuren C24 geschaafd circa 36x220mm	38	225			18	242	303	350	163	182	138			
Vuren C24 geschaafd circa 38x235mm	38	235		55			55	116	98	110	161			
Vuren C24 geschaafd circa 36x245mm	38	250					77	111	95	65	148			
Geschaafd, 038X275, Vuren, C24	38	275										290		
Vuren 47x125mm C24 geschaafd op 44x120mm hakregel	47	125									9			
Geschaafd, 075X125, Vuren, C, Ronde Muurplaat	75	125									14		48	
Geschaafd, 075X150, Vuren, C, Ronde Muurplaat	75	150									98			
Geschaafd, 075X200, Vuren, C, Ronde Muurplaat	75	200									150			

Gevingerlast	B	D	540	570	600	660	700	750	800	900	1000			
Gevingerlast KOMO C24, geschaafd op circa 30x170mm	32	175		93	105	146		191		9				
Gevingerlast KOMO C24, geschaafd op circa 30x195mm	32	200		117	82	97		31		9				
Gevingerlast KOMO C24, geschaafd op circa 30x220mm	32	225		37	36	138				33	70			
Gevingerlast KOMO C24, geschaafd op circa 30x245mm	32	250		297	326	116		45		1	52			
Gevingerlast KOMO C24, geschaafd op circa 30x270mm	32	275		130						74				
Gevingerlast KOMO C24, geschaafd op circa 38x170mm	38	170		12		63		154		161				
Gevingerlast KOMO C24, geschaafd op circa 36x170mm	38	175		27	40	100		142		145				
Gevingerlast KOMO C24, geschaafd op circa 38x184mm	38	184		329		353		75		354				
Gevingerlast KOMO C24, geschaafd op circa 36x195mm	38	200		140	202	163		139		143				
Gevingerlast KOMO C24, geschaafd op circa 36x220mm	38	225		9	548	122		19		3				
Gevingerlast KOMO C24, geschaafd op circa 38x235mm	38	235	9			4		2						
Gevingerlast KOMO C24, geschaafd op circa 36x245mm	38	250		7		48		65		162				
Gevingerlast KOMO C24, geschaafd op circa 36x270mm	38	275		372	433	159		7		12				
Gevingerlast KOMO C24, geschaafd op circa 38x285mm	38	285		8	201					199				
Gevingerlast KOMO C24, geschaafd op circa 44x270 mm	47	275			36	51		45		26	39			