



Geschaafd	B	D	270	300	330	360	390	420	450	480	510	540	570	600
Geschaafd, 011x038, Vuren, C, Geegaliseerd	11	38					10510	10874	15400		1787			
Geschaafd, 022x050, Vuren, Ventilatielat gewolman...	22	50					832	1291	1031	541				
Vuren C 21.5x48 geëgaliseerd en gebost	22	50					6		1890	1055	374	4572	23	
Vuren geschaafd op 28x45mm gewolmaniseerd	32	50							1304		193			
Vuren C geschaafd circa 30x45mm	32	50		1				338		382	517	182		
Vuren ventilatielat 28x45 mm hoh 400mm 7x40 gewo...	32	50					849				1175			
Vuren C geschaafd circa 30x58 mm	32	63		111		421		381		59		450		
Vuren C geschaafd circa 30x70mm	32	75						225		215		2		
Vuren KOMO C geschaafd circa 30x120mm	32	125		78	76	379	237		31	1	3			
Vuren KOMO C geschaafd circa 30x145mm	32	150			83	97	187	193	568	329	248	99		
Vuren C24 geschaafd circa 30x170mm	32	175				63		249	79	211	194	44		
Vuren C24 geschaafd circa 30x195mm	32	200				1	153	34	281	163	91			
Vuren C24 geschaafd circa 30x220mm	32	225				138	186	329	260	123	250	147		
Vuren C24 geschaafd circa 30x245mm	32	250				160	108	313	248	311				
Vuren C24 geschaafd circa 38x089mm	38	89		1	5	76	274	647	371	388	47	288		
Vuren C24 geschaafd circa 38x120mm	38	120			45	222	320	185	159	298	409	113		
Vuren C24 geschaafd circa 38x140mm	38	140			32	138	135	187		717	253			
Vuren C24 geschaafd circa 38x170mm	38	170				384	62	467		169		564		70
Vuren C24 geschaafd circa 36x170mm	38	175				16	81	190	47	113	32	215		
Vuren C24 geschaafd circa 38x184mm	38	184					86	96	92	29	47	216		
Vuren C24 geschaafd circa 36x195mm	38	200						251	55	163	55			
Vuren C24 geschaafd circa 36x220mm	38	225					62	93	242	177	247	18		
Vuren C24 geschaafd circa 38x235mm	38	235		164	473	864	146	149	288	269	162	40		38
Vuren C24 geschaafd circa 36x245mm	38	250				99			135	57	180			
Vuren C24 geschaafd circa 36x270mm	38	275										146		
Vuren C geschaafd circa 44x70mm	47	75	124	434	458	225	170	236	108	565	162	696		65
Vuren C24, geschaafd 44x95mm	47	100		176	121	123	888	103	158		216			
Vuren C24, geschaafd 44x120mm	47	125		1	54	92	140	23	52	134	154	213		
Vuren C geschaafd op 44x120mm hakregel	47	125										59		
Vuren C24, geschaafd 44x145mm	47	150		69	65	39	121	107	112		84			
Vuren C24, geschaafd op 44x170mm	47	175		67		114	105	72	109	129				
Vuren C24, geschaafd op 44x195mm	47	200		112	57	242		24	84	123	85	62		
Vuren C24, geschaafd op 44x220mm	47	225		5	37	18	135		3		60	212		
Vuren C24, geschaafd op 44x245mm	47	250		36	45	116	69	48	96	73	72			
Vuren C24 geschaafd circa 58x155mm	63	160		50	43		101	40	1	56	108	49		
Vuren C geschaafd circa 70x120mm ronde muurplaat	75	125									211			

Gevingerlast	B	D	540	570	600	660	700	750	800	850	900	1000		
Gevingerlast KOMO C24, geschaafd op circa 30x170mm	32	175						71						
Gevingerlast KOMO C24, geschaafd op circa 30x195mm	32	200		336	329	66		3			9			
Gevingerlast KOMO C24, geschaafd op circa 30x220mm	32	225				124		136			21	80		
Gevingerlast KOMO C24, geschaafd op circa 30x245mm	32	250		56	364	109		89						
Gevingerlast KOMO C24, geschaafd op circa 30x270mm	32	275		16	142	40		165					69	
Gevingerlast KOMO C24, geschaafd op circa 38x170mm	38	170		25	336	23		168			150			
Gevingerlast KOMO C24, geschaafd op circa 36x170mm	38	175		115	134	27		42			84			
Gevingerlast KOMO C24, geschaafd op circa 38x184mm	38	184		5		9		35			169			
Gevingerlast KOMO C24, geschaafd op circa 36x195mm	38	200		213	185	146		185			207			
Gevingerlast KOMO C24, geschaafd op circa 36x220mm	38	225		75	77			158	123		245			
Gevingerlast KOMO C24, geschaafd op circa 38x235mm	38	235	1278	168	217	284	208	397			448			
Gevingerlast KOMO C24, geschaafd op circa 36x245mm	38	250	2	270		47		107			155			
Gevingerlast KOMO C24, geschaafd op circa 36x270mm	38	275		267	274	365		30			274	45		
Gevingerlast KOMO C24, geschaafd op circa 38x285mm	38	285			342	246		268		112	243			
Gevingerlast KOMO C24, geschaafd op circa 44x270 mm	47	275		165	88	152		159			108	66		
Gevingerlast KOMO C24, geschaafd op circa 58x155mm	63	160		93	18	79		47			76			
Gevingerlast KOMO C24, geschaafd op circa 70x170mm	75	175		96				122			90			
Gevingerlast KOMO C24, geschaafd op circa 70x195mm	75	200		96		1		24			169			
Gevingerlast KOMO C24, geschaafd op circa 70x220mm	75	225		65	65	51		2			78			
Gevingerlast KOMO C24, geschaafd op circa 70x245mm	75	250		12	94	77		62			51			