

Geschaafd	B	D	113	123	255	270	300	330	360	390	420	450	480	510	540	570	600
Geschaafd, 011x038, Vuren, C, Geegaliseerd	11	38										735					
Vuren C 21.5x48 geëgaliseerd en gebost	22	50			3510	3049	2477	2176	1420	1640	3287	916	764	5221	3423		
Vuren C geschaafd circa 30x45mm	32	50					525		615		213		828	15	187		
Vuren ventilatielat 28x45 mm hoh 400mm 7x40 gewolmaniseerd	32	50										1349		396			
Vuren C geschaafd circa 30x58 mm	32	63					607		348		509		632	1230	2115		
Vuren C geschaafd circa 30x70mm	32	75							432		48		106	889			
Vuren KOMO C geschaafd circa 30x120mm	32	125					426		15		379		233	289	283		
Vuren KOMO C geschaafd circa 30x145mm	32	150							202		134	226			42		
Vuren C24 geschaafd circa 30x170mm	32	175						57	117		295		99	57	597		
Vuren C24 geschaafd circa 30x195mm	32	200								230	177	79	68	141	142		
Vuren C24 geschaafd circa 30x220mm	32	225							184	240	189	150	308	328	148	162	
Vuren C24 geschaafd circa 30x245mm	32	250							1	128	207	264	258	229	125		
Geschaafd 32x275 op 30x270 C24 LT	32	275											6				
Vuren C24 geschaafd circa 38x089mm	38	89	1229	490			586		340	418	778	336	1219	329	4459		5939
Vuren C24 geschaafd circa 38x120mm	38	120					468	224	173	218		234	266	230	302		4027
Vuren C24 geschaafd circa 38x140mm	38	140					864			121	84	301	222		615		270
Vuren C24 geschaafd circa 38x170mm	38	170							103		60			99	115	336	1116
Vuren C24 geschaafd circa 36x170mm	38	175								143	96	174	124	75	99		
Vuren C24 geschaafd circa 38x184mm	38	184					78	31	4	283	66	192	304	301	588	3	498
Vuren C24 geschaafd circa 36x195mm	38	200							1		85	140	249	274	267		
Vuren C24 geschaafd circa 36x220mm	38	225						282				131	178	35	114		
Vuren C24 geschaafd circa 38x235mm	38	235					56	209	62	90	386	276	382	408	1326	5	254
Vuren C24 geschaafd circa 36x245mm	38	250							13	120	143	56	1	185	6		
Vuren C24 geschaafd circa 36x270mm	38	275											30		13		
Vuren C geschaafd circa 44x70mm	47	75					985	1099	459	663	796	333	250	234	69		
Vuren C24, geschaafd 44x95mm	47	100							108	360	272	218	15	27			
Vuren C geschaafd op 44x120mm hakregel	47	125												1			
Vuren C24, geschaafd 44x120mm	47	125					400	108		59	71		163	224	103		
Vuren C24, geschaafd 44x145mm	47	150					77		92	154	103	168	256	209	208		
Vuren C24, geschaafd op 44x170mm	47	175						147	116	56	136	282	91		13		

Geschaafd	B	D	113	123	255	270	300	330	360	390	420	450	480	510	540	570	600
Vuren C24, geschaafd op 44x195mm	47	200						37	16	29	137	105	127	149	110		
Vuren C24, geschaafd op 44x220mm	47	225					27				82	86	149	139	107		
Vuren C24, geschaafd op 44x245mm	47	250					50	46	242	88	80	40	247	206	214		
Vuren C24 geschaafd circa 58x155mm	63	160					108		143		86		138	253	222		
Vuren C geschaafd circa 70x120mm ronde muurplaat	75	125												31	35		
Vuren C geschaafd circa 70x145mm ronde muurplaat	75	150												98			
Vuren C24 geschaafd circa 70x170mm	75	175					31	76	369	141	61	66	82	1	134		
Vuren C24 geschaafd circa 70x195mm	75	200						35	30		84	55	128	107	138		
Vuren C geschaafd circa 70x195mm ronde muurplaat	75	200												40			
Vuren C24 geschaafd circa 70x220mm	75	225					33	27	52		185	89	148		272		
Vuren C24 geschaafd circa 70x245mm	75	250						58			100	65	30	52	94		

Gevingerlast	B	D	570	600	660	750	900	1000						
Gevingerlast KOMO C24, geschaafd op circa 30x170mm	32	175	238	240	149	235	190							
Gevingerlast KOMO C24, geschaafd op circa 30x195mm	32	200		1	21	40	85							
Gevingerlast KOMO C24, geschaafd op circa 30x220mm	32	225			83	145	258							
Gevingerlast KOMO C24, geschaafd op circa 30x245mm	32	250	130	206	237	168	383							
Gevingerlast KOMO C24, geschaafd op circa 30x270mm	32	275	117	203	342	189	406	202						
Gevingerlast KOMO C24, geschaafd op circa 38x170mm	38	170			148	162	107							
Gevingerlast KOMO C24, geschaafd op circa 36x170mm	38	175	130	21	69	85	47							
Gevingerlast KOMO C24, geschaafd op circa 38x184mm	38	184			86	66	140							
Gevingerlast KOMO C24, geschaafd op circa 36x195mm	38	200	159	139	93	101	93							
Gevingerlast KOMO C24, geschaafd op circa 36x220mm	38	225	269	207	156	7	415							
Gevingerlast KOMO C24, geschaafd op circa 38x235mm	38	235	5	192	300	941	411	9						
Gevingerlast KOMO C24, geschaafd op circa 36x245mm	38	250	151	399	310	102		66						
Gevingerlast KOMO C24, geschaafd op circa 36x270mm	38	275	145	222	152	94	122	106						
Gevingerlast KOMO C24, geschaafd op circa 38x285mm	38	285	126	100	172	123	9							
Vuren C24, KOMO gevingerlast op circa 44x170 mm	47	175	55	108	100	77	90							
Vuren C24, KOMO gevingerlast op circa 44x195 mm	47	200	130	109	115	19	110							
Vuren C24, KOMO gevingerlast op circa 44x220 mm	47	225	108	117	163	174	55							
Vuren C24, KOMO gevingerlast op circa 44x245 mm	47	250	96	96	96	96	87							
Gevingerlast KOMO C24, geschaafd op circa 44x270 mm	47	275	27	144			53	58						
Gevingerlast KOMO C24, geschaafd op circa 58x155mm	63	160	90	56	94	56	56							
Gevingerlast KOMO C24, geschaafd op circa 70x170mm	75	175	41	7	12	68	74							
Gevingerlast KOMO C24, geschaafd op circa 70x195mm	75	200	61	127	24	93	121							
Gevingerlast KOMO C24, geschaafd op circa 70x220mm	75	225	94	122	105	39	97							
Gevingerlast KOMO C24, geschaafd op circa 70x245mm	75	250	84	35	90	81	83							
Gevingerlast, 075X275, Vuren, C24, KOMO	75	275	36		48	24	3							