

Geschaafd	B	D	255	270	300	330	360	390	420	450	480	510	540	570	600
Geschaafd, 011x038, Vuren, C, Geegaliseerd	11	38							5600	7560	8740				
Geschaafd, 022x050, Vuren, Ventilatielat gewolmaniseerd	22	50			10164										
Vuren C 21.5x48 geëgaliseerd en gebost	22	50	1310	2480	2690	6	2920	1030	1667	1754	1549	928	4663		
Vuren ventilatielat 28x45 mm hoh 400mm 7x40 gewolmaniseerd	32	50								1349					
Vuren C geschaafd circa 30x45mm	32	50			260		582		914		737	655	853		
Vuren C geschaafd circa 30x58 mm	32	63			343		347		312		240	21	1006		
Vuren C geschaafd circa 30x70mm	32	75					487		180		270	668			
Vuren KOMO C geschaafd circa 30x120mm	32	125			413		237		56		130	151	305		
Vuren KOMO C geschaafd circa 30x145mm	32	150					229		288	226		412			
Vuren C24 geschaafd circa 30x170mm	32	175				57			185		133	356			
Vuren C24 geschaafd circa 30x195mm	32	200					160	150	76	39	9	575	203		
Vuren C24 geschaafd circa 30x220mm	32	225					159	240	181	150	278	184	453	162	
Vuren C24 geschaafd circa 30x245mm	32	250								208	73	41			
Geschaafd 32x275 op 30x270 C24 LT	32	275									123		27		
Vuren C24 geschaafd circa 38x089mm	38	89			586		307	418	294	332	1012		4395		4568
Vuren C24 geschaafd circa 38x120mm	38	120			437	224	214	199	266	256	55	32	66		4836
Vuren C24 geschaafd circa 38x140mm	38	140			513	42		121		301	137	176	1653		
Vuren C24 geschaafd circa 38x170mm	38	170					67		111		2	1	756	16	463
Vuren C24 geschaafd circa 36x170mm	38	175						143	73	174	111	243	216		
Vuren C24 geschaafd circa 38x184mm	38	184				8		86	16		289	208	5		53
Vuren C24 geschaafd circa 36x195mm	38	200							279	280	179	274	253		
Vuren C24 geschaafd circa 36x220mm	38	225				282	136		240	88	160	338	211		
Vuren C24 geschaafd circa 38x235mm	38	235			56	6	61	44	517	419	946	1108	3129	169	293
Vuren C24 geschaafd circa 36x245mm	38	250						120	122	20	217	93	490		
Vuren C geschaafd circa 44x70mm	47	75			905	1099	415	663	728	333	334	233			
Vuren C24, geschaafd 44x95mm	47	100			304		384	360	215	218	47		5		
Vuren C24, geschaafd 44x120mm	47	125			400	80	79	59	125		32	141	190		
Vuren C geschaafd op 44x120mm hakregel	47	125										1	158		
Vuren C24, geschaafd 44x145mm	47	150			77		1	154	63	91	187	111			
Vuren C24, geschaafd op 44x170mm	47	175				147	102	56	93	282	139	132	202		

Geschaafd	B	D	255	270	300	330	360	390	420	450	480	510	540	570	600
Vuren C24, geschaafd op 44x195mm	47	200				37	168	29	128	105	108	504	38		
Vuren C24, geschaafd op 44x220mm	47	225			27		99		152	86	28	123	186		
Vuren C24, geschaafd op 44x245mm	47	250			50	46	207	88	59	38	187	87	108		
Vuren C24 geschaafd circa 58x155mm	63	160			81		127		96		101	195	71		
Vuren C geschaafd circa 70x120mm ronde muurplaat	75	125										256	24		
Vuren C geschaafd circa 70x145mm ronde muurplaat	75	150										48			
Vuren C24 geschaafd circa 70x170mm	75	175			67	40	166	99		66	79	121			
Vuren C24 geschaafd circa 70x195mm	75	200			28	35	108		29	55	62	24	75		
Vuren C geschaafd circa 70x195mm ronde muurplaat	75	200										15			
Vuren C24 geschaafd circa 70x220mm	75	225			48	27	57	54	147	183	116	109	22		
Vuren C24 geschaafd circa 70x245mm	75	250				55			2	65					

Gevingerlast	B	D	570	600	660	700	750	900	1000					
Gevingerlast KOMO C24, geschaafd op circa 30x170mm	32	175	223	164	280		150	164						
Gevingerlast KOMO C24, geschaafd op circa 30x195mm	32	200	124	200	192		153	221						
Gevingerlast KOMO C24, geschaafd op circa 30x220mm	32	225	325	131	206		219	85						
Gevingerlast KOMO C24, geschaafd op circa 30x245mm	32	250			159			2						
Gevingerlast KOMO C24, geschaafd op circa 30x270mm	32	275	60	29	98		54	166	127					
Gevingerlast KOMO C24, geschaafd op circa 38x170mm	38	170			135		127	23						
Gevingerlast KOMO C24, geschaafd op circa 36x170mm	38	175	165	243	215		95	190						
Gevingerlast KOMO C24, geschaafd op circa 38x184mm	38	184		366	379		140	68						
Gevingerlast KOMO C24, geschaafd op circa 36x195mm	38	200	156	22	22		81	87						
Gevingerlast KOMO C24, geschaafd op circa 36x220mm	38	225	215	207	346		302	324						
Gevingerlast KOMO C24, geschaafd op circa 38x235mm	38	235	62	16	300	336	595	170	19					
Gevingerlast KOMO C24, geschaafd op circa 36x245mm	38	250	225	209	317		310	312	23					
Gevingerlast KOMO C24, geschaafd op circa 36x270mm	38	275	17	66	312		285	196						
Gevingerlast KOMO C24, geschaafd op circa 38x285mm	38	285	116	9	151		184	382	51					
Vuren C24, KOMO gevingerlast op circa 44x170 mm	47	175	133	108	100		160	90						
Vuren C24, KOMO gevingerlast op circa 44x195 mm	47	200	56	158	167		176	110						
Vuren C24, KOMO gevingerlast op circa 44x220 mm	47	225	104	117	141		174	55						
Vuren C24, KOMO gevingerlast op circa 44x245 mm	47	250	89	91	122		92	79						
Gevingerlast KOMO C24, geschaafd op circa 44x270 mm	47	275	97	106	116		50	101	1					
Gevingerlast KOMO C24, geschaafd op circa 58x155mm	63	160	90	51	38		56	56						
Gevingerlast KOMO C24, geschaafd op circa 70x170mm	75	175	53	77	166		92	51						
Gevingerlast KOMO C24, geschaafd op circa 70x195mm	75	200	89	83	152		93	173						
Gevingerlast KOMO C24, geschaafd op circa 70x220mm	75	225	66	183	189		72	57						
Gevingerlast KOMO C24, geschaafd op circa 70x245mm	75	250	2	3	72		48	60						
Gevingerlast, 075X275, Vuren, C24, KOMO	75	275	89	39	39			39						