

Geschaafd	B	D	255	270	300	330	360	390	420	450	480	510	540	570	600
Geschaafd, 011x038, Vuren, C, Geegaliseerd	11	38							5600	7560	9240				
Geschaafd, 022x050, Vuren, Ventilatielat gewolmaniseerd	22	50			10164										
Vuren C 21.5x48 geëgaliseerd en gebost	22	50	1310	2480	2240	1226	1110	1030	1167	1574	1379		4063		
Vuren ventilatielat 28x45 mm hoh 400mm 7x40 gewolmaniseerd	32	50								997					
Vuren C geschaafd circa 30x45mm	32	50			252		566		912		735	655	853		
Vuren C geschaafd circa 30x58 mm	32	63			343		347		59		80		569		
Vuren C geschaafd circa 30x70mm	32	75					467		173		270	620			
Vuren KOMO C geschaafd circa 30x120mm	32	125			162		236		4		123	125	296		
Vuren KOMO C geschaafd circa 30x145mm	32	150					198		283	226		326			
Vuren C24 geschaafd circa 30x170mm	32	175				57			183		43	134			
Vuren C24 geschaafd circa 30x195mm	32	200					158	150	49	39		480	163		
Vuren C24 geschaafd circa 30x220mm	32	225					152	240	137	150	272	184	453	162	
Vuren C24 geschaafd circa 30x245mm	32	250								176	47	19			
Geschaafd 32x275 op 30x270 C24 LT	32	275											22		
Vuren C24 geschaafd circa 38x089mm	38	89			86		66	418	280	332	996		3857		4474
Vuren C24 geschaafd circa 38x120mm	38	120			437	224	214	199	260	178	8	24			4555
Vuren C24 geschaafd circa 38x140mm	38	140			513	42		121		301	123	170	1504		
Vuren C24 geschaafd circa 38x170mm	38	170					1		111		2	1	605	16	291
Vuren C24 geschaafd circa 36x170mm	38	175						143	45	174	109	243	216		
Vuren C24 geschaafd circa 38x184mm	38	184				8		6	233		232	163			
Vuren C24 geschaafd circa 36x195mm	38	200							277	280	175	267	249		
Vuren C24 geschaafd circa 36x220mm	38	225				282	135		240	88	160	338	207		
Vuren C24 geschaafd circa 38x235mm	38	235			56	6			390	419	942	877	2650	169	15
Vuren C24 geschaafd circa 36x245mm	38	250						120	122	20	217	61	467		
Vuren C geschaafd circa 44x70mm	47	75			863	1099	374	663	717	333	282	1	17		
Vuren C24, geschaafd 44x95mm	47	100			293		377	360	215	218					
Vuren C24, geschaafd 44x120mm	47	125			400	63	51	59	123			94	187		
Vuren C geschaafd op 44x120mm hakregel	47	125										1	147		
Vuren C24, geschaafd 44x145mm	47	150			77			154	52	91	187	99			
Vuren C24, geschaafd op 44x170mm	47	175				147	100	56	87	282	121	132	68		

Geschaafd	B	D	255	270	300	330	360	390	420	450	480	510	540	570	600
Vuren C24, geschaafd op 44x195mm	47	200				37	156	29	122	105	108	504	35		
Vuren C24, geschaafd op 44x220mm	47	225			27		99		150	86	28	123	185		
Vuren C24, geschaafd op 44x245mm	47	250			50	46	195	88	43	38	187	87	107		
Vuren C24 geschaafd circa 58x155mm	63	160			75		127		96		101	195	71		
Vuren C geschaafd circa 70x120mm ronde muurplaat	75	125										256	24		
Vuren C geschaafd circa 70x145mm ronde muurplaat	75	150										48			
Vuren C24 geschaafd circa 70x170mm	75	175			67	40	162	99		66	71	119	1		
Vuren C24 geschaafd circa 70x195mm	75	200			27	35	108		29	55	62	24	59		
Vuren C geschaafd circa 70x195mm ronde muurplaat	75	200										15			
Vuren C24 geschaafd circa 70x220mm	75	225			48	27	57	54	131	183	115	109	42		
Vuren C24 geschaafd circa 70x245mm	75	250				51	60	60	72	39	162			74	

Gevingerlast	B	D	570	600	660	700	750	900	1000					
Gevingerlast KOMO C24, geschaafd op circa 30x170mm	32	175	205	156	252		125	158						
Gevingerlast KOMO C24, geschaafd op circa 30x195mm	32	200	123	167	169		149	219						
Gevingerlast KOMO C24, geschaafd op circa 30x220mm	32	225	323	49	206		219	85						
Gevingerlast KOMO C24, geschaafd op circa 30x245mm	32	250			119									
Gevingerlast KOMO C24, geschaafd op circa 30x270mm	32	275			23									
Gevingerlast KOMO C24, geschaafd op circa 38x170mm	38	170			135		111	20						
Gevingerlast KOMO C24, geschaafd op circa 36x170mm	38	175	160	243	193		77	190						
Gevingerlast KOMO C24, geschaafd op circa 38x184mm	38	184		275	378		113	50						
Gevingerlast KOMO C24, geschaafd op circa 36x195mm	38	200	151	15	19		71	87						
Gevingerlast KOMO C24, geschaafd op circa 36x220mm	38	225	214	207	342		298	318						
Gevingerlast KOMO C24, geschaafd op circa 38x235mm	38	235	59	5	21	280	578	34	19					
Gevingerlast KOMO C24, geschaafd op circa 36x245mm	38	250	159	209	186		294	200	23					
Gevingerlast KOMO C24, geschaafd op circa 36x270mm	38	275		12	102			6						
Gevingerlast KOMO C24, geschaafd op circa 38x285mm	38	285	107	8	223		158	373	47					
Vuren C24, KOMO gevingerlast op circa 44x170 mm	47	175	133	108	100		160	90						
Vuren C24, KOMO gevingerlast op circa 44x195 mm	47	200	56	158	167		176	110						
Vuren C24, KOMO gevingerlast op circa 44x220 mm	47	225	101	117	141		174	55						
Vuren C24, KOMO gevingerlast op circa 44x245 mm	47	250	85	90	122		79	78						
Gevingerlast KOMO C24, geschaafd op circa 44x270 mm	47	275	88	104	111		43	53	1					
Gevingerlast KOMO C24, geschaafd op circa 58x155mm	63	160	90	51	38		56	56						
Gevingerlast KOMO C24, geschaafd op circa 70x170mm	75	175	47	63	165		61	51						
Gevingerlast KOMO C24, geschaafd op circa 70x195mm	75	200	79	5	152		89	173						
Gevingerlast KOMO C24, geschaafd op circa 70x220mm	75	225	66	183	189		69	57						
Gevingerlast KOMO C24, geschaafd op circa 70x245mm	75	250	2		47		44	60						
Gevingerlast, 075X275, Vuren, C24, KOMO	75	275	84	39	39			39						