

Geschaafd	B	D	255	270	300	330	360	390	420	450	480	510	540	570	600
Geschaafd, 011x038, Vuren, C, Geegaliseerd	11	38							5600	7560	9240				
Geschaafd, 022x050, Vuren, Ventilatielat gewolmaniseerd	22	50						1100	5107	100					
Vuren C 21.5x48 geëgaliseerd en gebost	22	50	1310		1699	1996	1460	450	2757	18	1834	2135	48		
Vuren ventilatielat 28x45 mm hoh 400mm 7x40 gewolmaniseerd	32	50								997					
Vuren C geschaafd circa 30x45mm	32	50			246		562		153		88	619	843		
Vuren C geschaafd circa 30x58 mm	32	63			339		212		561		392	37	596		
Vuren C geschaafd circa 30x70mm	32	75					355		148		237	515	276		
Vuren KOMO C geschaafd circa 30x120mm	32	125			17		25		5			2	9		
Vuren KOMO C geschaafd circa 30x145mm	32	150					8		118	226	170	313			
Vuren C24 geschaafd circa 30x170mm	32	175				57			115		210	3	33		
Vuren C24 geschaafd circa 30x195mm	32	200						150	130	39	152	305			
Vuren C24 geschaafd circa 30x220mm	32	225					89	240	117	150	243	155	406	162	
Vuren C24 geschaafd circa 30x245mm	32	250							105	176	167	29	197		
Geschaafd 32x275 op 30x270 C24 LT	32	275									374	132	412		
Vuren C24 geschaafd circa 38x089mm	38	89			86		318	418	232	332	915	13			4033
Vuren C24 geschaafd circa 38x120mm	38	120				224	77	199	208	168	337	141	2	126	4952
Vuren C24 geschaafd circa 38x140mm	38	140			93	42	73	121			109	111	257		398
Vuren C24 geschaafd circa 38x170mm	38	170							102		2	1	284	8	74
Vuren C24 geschaafd circa 36x170mm	38	175						143	19	174	93	238	196		
Vuren C24 geschaafd circa 38x184mm	38	184				122	100	150	103		107		1442	41	872
Vuren C24 geschaafd circa 36x195mm	38	200							261	280	130	267	248		
Vuren C24 geschaafd circa 36x220mm	38	225				282	100		208	88	9	298	110		
Vuren C24 geschaafd circa 38x235mm	38	235			78	6	41	324	521	558	882	945	3297	183	357
Vuren C24 geschaafd circa 36x245mm	38	250						120	83	20	57	85	343		
Vuren C24 geschaafd circa 36x270mm	38	275									193				
Vuren C geschaafd circa 44x70mm	47	75			4948	1099	260	663	317	333	432	420	1228		
Vuren C24, geschaafd 44x95mm	47	100			130		357	360	204	218	201	413			
Vuren C24, geschaafd 44x120mm	47	125			310	27	176	59	109			205	304		
Vuren C geschaafd op 44x120mm hakregel	47	125										1	189		
Vuren C24, geschaafd 44x145mm	47	150					143	154	10	91	174	28			

Geschaafd	B	D	255	270	300	330	360	390	420	450	480	510	540	570	600
Vuren C24, geschaafd op 44x170mm	47	175				47	72	56	77	282	115		116		
Vuren C24, geschaafd op 44x195mm	47	200				37	158	29	128	105	86	504	137		
Vuren C24, geschaafd op 44x220mm	47	225			27		35		134	86	28	118	123		
Vuren C24, geschaafd op 44x245mm	47	250			50	46	193	88	25	38	174	78	132		
Vuren C24 geschaafd circa 58x155mm	63	160			66		121		72		84	195	70		
Vuren C geschaafd circa 70x120mm ronde muurplaat	75	125										157			
Vuren C geschaafd circa 70x145mm ronde muurplaat	75	150										95			
Vuren C24 geschaafd circa 70x170mm	75	175					98	99		66	14	30	11		
Vuren C24 geschaafd circa 70x195mm	75	200					67		21	55	1	14	9		
Vuren C geschaafd circa 70x195mm ronde muurplaat	75	200										15			
Vuren C24 geschaafd circa 70x220mm	75	225			44			44	131	183	107	109	6		
Vuren C24 geschaafd circa 70x245mm	75	250				11	18	60	70	39	162	96	28	74	

Gevingerlast	B	D	570	600	630	660	690	700	750	900	1000			
Gevingerlast KOMO C24, geschaafd op circa 30x170mm	32	175	177	128		232			265	60				
Gevingerlast KOMO C24, geschaafd op circa 30x195mm	32	200	156	161		152			167	362				
Gevingerlast KOMO C24, geschaafd op circa 30x220mm	32	225	313			159			215	157				
Gevingerlast KOMO C24, geschaafd op circa 30x245mm	32	250		17		118			148	244				
Gevingerlast KOMO C24, geschaafd op circa 30x270mm	32	275		621	64	78	64		416	570				
Gevingerlast KOMO C24, geschaafd op circa 38x170mm	38	170				127			85	280				
Gevingerlast KOMO C24, geschaafd op circa 36x170mm	38	175	151	238		193			76	152				
Gevingerlast KOMO C24, geschaafd op circa 38x184mm	38	184		41		314			88					
Gevingerlast KOMO C24, geschaafd op circa 36x195mm	38	200	146	72		54			128	197				
Gevingerlast KOMO C24, geschaafd op circa 36x220mm	38	225	204	549		189			237	125				
Gevingerlast KOMO C24, geschaafd op circa 38x235mm	38	235	104	508		130		406	47					
Gevingerlast KOMO C24, geschaafd op circa 36x245mm	38	250	22	209		77			85		110			
Gevingerlast KOMO C24, geschaafd op circa 36x270mm	38	275	52	109		23			97		56			
Gevingerlast KOMO C24, geschaafd op circa 38x285mm	38	285	144	205		150			184	262	57			
Vuren C24, KOMO gevingerlast op circa 44x170 mm	47	175	117	106		95			160	77				
Vuren C24, KOMO gevingerlast op circa 44x195 mm	47	200	56	135		131			176	110				
Vuren C24, KOMO gevingerlast op circa 44x220 mm	47	225	95	117		141			174	55				
Vuren C24, KOMO gevingerlast op circa 44x245 mm	47	250	77	88		70			70	65				
Gevingerlast KOMO C24, geschaafd op circa 44x270 mm	47	275	37	96		49			7	50	1			
Gevingerlast KOMO C24, geschaafd op circa 58x155mm	63	160	90	51		38			56	25				
Gevingerlast KOMO C24, geschaafd op circa 70x170mm	75	175	10	53		141			8	1				
Gevingerlast KOMO C24, geschaafd op circa 70x195mm	75	200	56	145		105			73	95				
Gevingerlast KOMO C24, geschaafd op circa 70x220mm	75	225		134		152			62	57				
Gevingerlast KOMO C24, geschaafd op circa 70x245mm	75	250	6			47			5	4				
Gevingerlast, 075X275, Vuren, C24, KOMO	75	275	74	38		39			16					